

The northwest corner of Section 34-17-3 was established by Surveyor Wm. B. Laughlin in 1820 as a post set with these witnesses: 10" beech N 35 degrees E 26 links 3" dogwood N 68 degrees E 5 links per Marion County Atlas pg. 8. Volume 2, page 249 original field books of Marion County.

On May 27, 1850, D.B. Hosbrook does not call the monument but takes these witnesses: 8" sugar S 26 degrees E 24 2/3 links, 32" walnut S 55 degrees E 80 links (Book 1. pg. 72).

November 1894, Paul Julian states "stone already set at the northeast corner of Section 33-17-4 (p.39 Washington Township Legal Survey Book.

May 14, 1925 survey by George Schmidt measures 2669.0 feet between the W Quarter of Section 27-17-4 S to the northwest corner of 34-17-4. Arb maps distance is 2669.61 and G.P.S. inverse is 2669.70.

Delaware Trails Subdivision (Plat Book 30, pg. 95, recorded August 17, 1956) by E. F. Apple P.E. records a distance of 1335.5 feet from a point in Grandview Drive E to the northwest corner of 34-17-3. MCSO recovered Apple's point and inversed 1335.50 feet to the stone believed to be the northwest corner of 34-17-3.

The same plat references a point 1336.5 feet S to the northwest corner, and MCSO recovered a 5/8" re-bar 1336.87 feet S of the stone.

The arb map distance northwest corner to North Quarter corner is 2650.0 and GPS inversed by MCSO was 2649.99.

The arb map distance for 27-17-3 Southwest Quarter is 2645.55, 4.45 feet different then the north line of 34-17-3.

17033401		
REF.	DISTANCE	DESCRIPTION
1.	12.85	Mag nail w/brass washer N multi scrub tree 10"up
2.	4.93'	Mag nail w/bw N 18" honey locus 8"up
3.	9.10'	Mag nail w/washer F multi scrub tree 10"up
		The state of the s